

Type		HDIQ 4
Order number		380 400
EAN-Code		4026187240868
Encoding		
Video encoding		MPEG2, MPEG4 AVC/H.264
Input		HDMI*4 (or SDI*4)
Resolution		1920*1080_60P, 1920*1080_50P (for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i
Low delay		Normal, mode 1, mode 2
Audio encoding		MPEG1 Layer II, MPEG2-AAC, MPEG4-AAC, AC-3 2.0
Sample rate	[kHz]	48
Bit rate	[kbps]	64, 96, 128, 192, 256, 320
Modulation		
Standard		J.83A , J.83B, J.83C
MER	[dB]	≥ 42
RF Frequency		4 carriers combined output; 30 - 960 MHz, 1 kHz steps
RF output level	[dbm]	-30...-10 (77-97 dμV), 0, 1dB steps
Symbol rate	[MSPS]	5,000 - 9,000 adjustable
Constellation		J.83A: 16 / 32 / 64 / 128 / 256QAM; J.83B and J.83C: 64 / 256QAM
Bandwidth		J.83A: 8 M; J.83B and J.83C: 6 M
System		
Local interface		LCD + control buttons
Remote management		WEB interface
Outputs		ASI out (BNC type); 1 IP (4*SPTS or 1 MPTS) out over UDP, RTP/RTSP (RJ45, 100 M)
NMS interface		RJ45, 100 M
Language		English
Common data		
Power supply	[VAC]	100 - 240
Dimensions	[mm]	420 x 400 x 44
Weight	[kg]	4,5
Ambient temperature	[°C]	0 - 45